



Table 8 – Dimensions Combination Drives

All combination drives have water cooling coils where required.
 All model numbers have a suffix "MS" & "TYPE" – Example: G125 MS Cent.

Model	M 40/60 M80/100	G40/60 G80	G100 G125	M150	M200	G150 G200A	G250	G300	G350 G400	F500/590 F750	P200	P20A
V	2	2	2	2	2-1/2	2-1/2	2-1/2	2-1/2	2-1/2	3	2 1/2	3
RCD Centrifugal	25-1/16	29-1/2	29-1/2	29-1/2	N/A	38	38	N/A	N/A	N/A	N/A	N/A
RCD Manual	23	27-1/2	27-1/2	27-1/2	31-1/8	33-9/16	33-9/16	33-9/16	35-1/4	45-3/8	33-9/16	31-1/2
RAG	33-1/2	38	38	38	38-9/16	45-9/16	45-9/16	45-9/16	45-3/8	59-3/4	45-9/16	43-5/8
RK Manual	7/8	7/8	7/8	7/8	1-1/16	1-1/16	1-1/16	1-1/16	1-1/16	1	1-1/16	1
RBD	16-1/2	20	20	20	20	24-7/16	24-7/16	24-7/16	24-7/16	24-1/2	24-7/16	24-1/2
RAJ	14-3/4	14-3/4	14-3/4	14-3/4	14-3/4	14-3/4	14-3/4	14-3/4	14-3/4	14 3/4 & 23	14-3/4	14 3/4 & 23
RBF	4-11/16	8-11/16	8-11/16	8-11/16	8-11/16	8-11/16	8-11/16	8-11/16	8-11/16	8-13/16	8-11/16	8-13/16
RAK	13.499	13.499	13.499	13.499	13.499	13.499	13.499	13.499	13.499	13.498	13.499	13.498
RO	12-3/4	12-3/4	12-3/4	12-3/4	12-3/4	12-13/16	12-13/16	12-13/16	12-13/16	12-1/4	12-13/16	12-1/4
RN	5/8	3/4	3/4	3/4	3/4	7/16	7/16	7/16	7/16	5/8	7/16	5/8
Appx. Net Wt. (lbs)	430	575	590	590	750	1010	1010	1010	1090	1600	865	1050
Domestic Wt. (lbs)	460	605	620	820	780	1045	1045	1045	1125	1675	900	1090
Export Wt. (lbs)	545	712	727	727	900	1230	1230	1230	1310	1865	1085	1195
Export Cube Ft.	10.7	13.0	13.0	13.0	13.9	34.0	34.0	34.0	34.0	57.0	34.0	19.0

All other dimensions and oil capacity are the same as standard gear drive.
 All models are standard sprag type non-reverse except centrifugal, which has no non-reverse protection.
 Contact factory for vertical speeds other than 1760 rpm.